

**PRB CLASSIC TAL - PRBCTAL**

**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name : PRB CLASSIC TAL

Product code : PRBCTAL.

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Coating

**1.3. Details of the supplier of the safety data sheet**

Registered company name : PRB S.A.

Address : 16 RUE DE LA TOUR CS 10018 . 85150. LES ACHARDS. FRANCE.

Telephone : 02 51 98 10 10. Fax : 02 51 98 10 21.

contact@prb.fr

**1.4. Emergency telephone number : 33(0)1 45 42 59 59.**

Association/Organisation : INRS.

**SECTION 2 : HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

**2.2. Label elements**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS05



GHS07

Signal Word :

DANGER

Product identifiers :

EC 266-043-4

CIMENT PORTLAND CEM 1 52.5

EC 215-137-3

HYDROXYDE DE CALCIUM (CHAUX ETEINTE)

Hazard statements :

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H318

Causes serious eye damage.

Precautionary statements - General :

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P302 + P352

IF ON SKIN: Wash with plenty of water/...

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P315

Get immediate medical advice/attention.

P333 + P313

If skin irritation or rash occurs: Get medical advice/attention.

**PRB CLASSIC TAL - PRBCTAL**

Precautionary statements - Disposal :

P501 Dispose of contents/container to ...

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

When mixed with water, the cement paste obtained has a high pH (12-13); then it can irritate the skin in case of prolonged contact and can cause eyes damage if splashed

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

**Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: PRB004 CAS: 65997-15-1 EC: 266-043-4  CIMENT PORTLAND CEM 1 52.5	GHS07, GHS05 Dgr Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 STOT SE 3, H335	[1]	10 <= x % < 25
INDEX: PRB003 CAS: 1317-65-3 EC: 215-279-6  CARBONATE DE CALCIUM		[1]	2.5 <= x % < 10
INDEX: PRB076 CAS: 1305-62-0 EC: 215-137-3 REACH: 01-2119475151-45  HYDROXYDE DE CALCIUM (CHAUX ETEINTE)	GHS07, GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335	[1]	2.5 <= x % < 10

(Full text of H-phrases: see section 16)

**Information on ingredients :**

[1] Substance for which maximum workplace exposure limits are available.

**Other data :**

The preparation contains siliceous sands including quartz as crystalline silica which have an inhalable alveolar fraction below 1%, then without classification.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures**

**In the event of exposure by inhalation :**

In case of inhalation, take the patient outdoor to fresh air.

Consult a doctor if breathing problem.

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, especially if it appears a redness, pain or visual discomfort.

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

Do not solvent or thriners

Swill the patient.

**In the event of swallowing :**

Do not give the patient anything orally.

If swallowed, rince mouth with water (only if the person is conscious).

Consult a doctor.

**PRB CLASSIC TAL - PRBCTAL**

---

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

---

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media**

No data available.

**5.2. Special hazards arising from the substance or mixture**

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Use independent breathing equipment (isolated unit).

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid any contact with the skin and eyes.

Avoid inhalation of dust.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Retrieve the product by mechanical means (sweeping/vacuuming) : do not generate dust.

**6.4. Reference to other sections**

No data available.

---

**SECTION 7 : HANDLING AND STORAGE**

**7.1. Precautions for safe handling**

Prevent the formation of dust.

In case of dust flight, wear a suitable dust mask.

**Fire prevention :**

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Avoid inhaling dust.

Avoid eye contact with this mixture at all times.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep in its original sealed packaging into normally dry atmosphere and sheltered.

**7.3. Specific end use(s)**

No data available.

**PRB CLASSIC TAL - PRBCTAL**

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

Average dust concentration of inhaled air

Total dust VME : 10 mg/m<sup>3</sup>

Respirable dust VME : 5 mg/m<sup>3</sup>

The preparation contains siliceous sands including quartz as crystalline silica which have an inhalable alveolar fraction below 1% , then without classification.

Alveolar dust can be generated in the work environment by the used operating procedure.

Therefore, the average concentration of respirable dust inhaled from the atmosphere during 8 hours should not exceed 0.1 mg/m<sup>3</sup> for quartz.

**Occupational exposure limits :**

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
1317-65-3	-	10	-	-	-	-
1305-62-0	-	5	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
65997-15-1	- ppm 4 mg/m <sup>3</sup>	- ppm - mg/m <sup>3</sup>			
1317-65-3	- ppm 4 mg/m <sup>3</sup>	- ppm - mg/m <sup>3</sup>			
1305-62-0	- ppm 5 mg/m <sup>3</sup>	- ppm - mg/m <sup>3</sup>			

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

HYDROXYDE DE CALCIUM (CHAUX ETEINTE) (CAS: 1305-62-0)

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Inhalation.  
Short term local effects.  
4 mg of substance/m<sup>3</sup>

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term local effects.  
1 mg of substance/m<sup>3</sup>

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Inhalation.  
Short term local effects.  
4 mg of substance/m<sup>3</sup>

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term local effects.  
1 mg of substance/m<sup>3</sup>

**Predicted no effect concentration (PNEC):**

HYDROXYDE DE CALCIUM (CHAUX ETEINTE) (CAS: 1305-62-0)

Environmental compartment:  
PNEC : Soil.  
1080 mg/kg

Environmental compartment:  
PNEC : Fresh water.  
0.49 mg/l

Environmental compartment:  
PNEC : Sea water.  
0.32 mg/l

Environmental compartment:  
PNEC : Waste water treatment plant.  
3 mg/l

**PRB CLASSIC TAL - PRBCTAL**

**8.2. Exposure controls**

**- Eye / face protection**

Wear goggles.

**- Hand protection**

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Protecting creams can be used for exposed skin. They should not be applied after contact with the product.

**- Body protection**

Wear working clothes to protect skin.

**- Respiratory protection**

Wear appropriate breathing equipment certified with EN standards if concentrations exceed exposure limits.

Example : dust mask

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state : Powder or dust.

To be translated (XML)

**Important health, safety and environmental information**

pH : Not stated.

Neutral.

Boiling point/boiling range : Not specified.

Flash point interval : Not relevant.

Vapour pressure (50°C) : Not relevant.

Density : > 1

Water solubility : Insoluble.

Melting point/melting range : Not specified.

Self-ignition temperature : Not specified.

Decomposition point/decomposition range : Not specified.

**9.2. Other information**

When the powder is mixed with water, this mixture takes a basic character and the PH is about 12.

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under conditions of handling and storage recommendations in Section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Avoid exposure to moisture.

**10.5. Incompatible materials**

Avoid contact with water (humid environment) during storage

**10.6. Hazardous decomposition products**

Thermal decomposition of additives from 200°C : formation of CO, CO<sub>2</sub>.

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

**11.1.1. Substances**

**Acute toxicity :**

CIMENT PORTLAND CEM 1 52.5 (CAS: 65997-15-1)

Dermal route : LD50 > 2000 mg/kg  
Species : Rabbit

HYDROXYDE DE CALCIUM (CHAUX ETEINTE) (CAS: 1305-62-0)

**PRB CLASSIC TAL - PRBCTAL**

Oral route : LD50 > 2000 mg/kg  
Species : Rat  
OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

Dermal route : LD50 > 2500 mg/kg  
Species : Rabbit  
OECD Guideline 402 (Acute Dermal Toxicity)

**Germ cell mutagenicity :**

HYDROXYDE DE CALCIUM (CHAUX ETEINTE) (CAS: 1305-62-0)  
Ames test (in vitro) : Negative.

**Carcinogenicity :**

HYDROXYDE DE CALCIUM (CHAUX ETEINTE) (CAS: 1305-62-0)  
Carcinogenicity Test : Negative.  
No carcinogenic effect.  
Species : Rat

**Reproductive toxicant :**

HYDROXYDE DE CALCIUM (CHAUX ETEINTE) (CAS: 1305-62-0)  
No toxic effect for reproduction

**11.1.2. Mixture**

**Skin corrosion/skin irritation :**

In case of prolonged contact, risk of skinburn (basic PH of the product when the powder is mixed with water).

**Serious damage to eyes/eye irritation :**

The mixture can cause irritation of the eyelids, cornea and can cause serious eyes lesions.

**Respiratory or skin sensitisation :**

The mixture can cause respiratory tract irritation, inflammation of the nasal mucosa.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

Prolonged or repeated contact with the preparation can cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.

---

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.1. Substances**

HYDROXYDE DE CALCIUM (CHAUX ETEINTE) (CAS: 1305-62-0)

Fish toxicity : LC50 = 50.6 mg/l  
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 49.1 mg/l  
Duration of exposure : 48 h

NOEC = 32 mg/l  
Species : Daphnia magna  
Duration of exposure : 14 days

Algae toxicity : ECr50 = 184.57 mg/l  
Duration of exposure : 72 h

Aquatic plant toxicity : NOEC = 48 mg/l  
Duration of exposure : 72 h

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

---

**PRB CLASSIC TAL - PRBCTAL**

---

**12.2. Persistence and degradability**

**12.2.1. Substances**

CIMENT PORTLAND CEM 1 52.5 (CAS: 65997-15-1)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

After setting of the product, its components are insoluble and definitely fixed.

---

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

---

**SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

---

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.

**- Container information:**

No data available.

**- Particular provisions :**

No data available.

**15.2. Chemical safety assessment**

No data available.

---

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**PRB CLASSIC TAL - PRBCTAL**

---

**Wording of the phrases mentioned in section 3 :**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

**Abbreviations :**

DNEL	: Derived No-Effect Level
PNEC	: Predicted No-Effect Concentration
ADR	: European agreement concerning the international carriage of dangerous goods by Road.
IMDG	: International Maritime Dangerous Goods.
IATA	: International Air Transport Association.
ICAO	: International Civil Aviation Organisation
RID	: Regulations concerning the International carriage of Dangerous goods by rail.
GHS05	: Corrosion
GHS07	: Exclamation mark